


H07RN-F

Approved Flexible tough rubber cable



Application

Flexible cable with good properties against general oils, weather inc UV, temperature range and mechanical stress.

Can be installed outdoors without risk of ultraviolet rays degrading the cables properties.

Good mechanical strength and resistant to moisture, however further protection should be used in high risk areas.

Construction

Conductor	Class 5 Flexible copper BS EN 60228
Insulation	EPR (Ethylene Propylene rubber) Type E14 BS EN 50363
Sheath	PCP (Polychloroprene) Type EM2 BS EN 50363
Approvals	Full European Harmonisation approval Hence suitable for BS requirement installations

Characteristics

Voltage Rating	450 / 750 V olt	BS EN 50525-2-21 (BS 7919)
Temperature	-30 Cto + 90 DegC fixed	BS EN 60811-2-1
	+90 Deg C in fixed protected	BS EN / IEC 60332-1-2
	-15 Deg C to +60 Deg C flexed	
Minimum Bend radius	6 x overall diameter flexed	HAR
Minimum Bend radius	4 x overall diameter Fixed	

Tel: 01753 687718 | Fax: 01753 251114 | sales@specialistcable.co.uk

Specialist Cable Supplies | Unit 10 | Coln Industrial Estate | Colnbrook | Slough | SL3 0NJ

www.specialistcable.co.uk Registered in England: 7664897