



Tel: 01753 687718
sales@specialistcable.co.uk

Fax: 01753 251114


Gen to BS5308 Part 1 Type 1 Overall SCR (UV) LSZH

Application

General purpose Industrial process, voice and data cable, for transmission of communication signals.

0.75mm x 1 Pair and 1 quad (four core)

CPR Compliant EN50575 -Class ECA



Construction

Conductor material: -	0.75mm - 24 x 0.19 plain copper gen to BS EN 60228
Insulation material:-	PE (Polyethylene) – nom od 2.40 (+/-0.10)mm
Core identification:	black, brown, blue, green
Screen material:	Al-Pet shield $\geq 115\%$ with tinned copper drain
Jacket:	Black (UV)LSZH, nominal O.D. 7.00 (+/-0.10)mm

*Packing:250m/ strong plwood reel with cable details in white ink marking every metre

Characteristics

Voltage rating	300V (test voltage 1000V)
Temperature rating	-15C to + 70°C static
Conductor DC resistance	< 27.36 Ω /Km @ 20degC
Insulation DC resistance	>200M Ω *Km
CPR Class Eca	Statement of Conformance It is hereby certified that any goods supplied that reference those above, conform to this specification unless otherwise noted I.Loades Director

Specialist Cable Supplies | Unit 10 | Coln Industrial Estate | Colnbrook | Slough | SL3 0NJ
www.specialistcable.co.uk Registered in England: 7664897